

# General Purpose PET and Tissue Tape



## Technical Data Sheet

Product	Steel Adhesion Strength	Temperature Resistance	Release Liner	Thickness
Tissue	1.2kg / 25mm	Min 0°C (32°F)   Max 50°C (122°F)	White Paper	0.08 mm / 0.315mil
PET	1.5kg / 25mm	Min 0°C (32°F)   Max 50°C (122°F)	White Paper	0.08 mm / 0.315mil

## Applications

Designed for bonding paper and cardboard (sulfate). Ideal for the graphic arts industry, splicing, laminating, and others.

## Features

- Tissue tape allows easy cutting.
- PET tape backing is more resistant to tension.

## Recommendations

- The surface to be bonded must be clean, dry, and free of grease, silicone, or dust.
- When applying the tape, the surfaces must be at a temperature between 18°C (64°F) and 30°C (86°F).
- It is necessary to apply pressure for 10 seconds on the bonded surfaces and wait 72 hours to achieve optimal adhesion before performing any tests.





## Available Sizes

Size (mm x mts)	Size (In x Yd)
6 x 50	0.24 x 54
9 x 50	0.35 x 54
12 x 50	0.47 x 54
18 x 50	0.71 x 54
24 x 50	0.94 x 54
48 x 50	1.89 x 54